

# EAO – Your Expert Partner for Human Machine Interfaces

## 45-2C36.2920.000 - Emergency stop switch - Actuator

### 45-2C36.2920.000 - Emergency stop switch - Actuator



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Attribute

|                      |                   |
|----------------------|-------------------|
| Design               | raised            |
| Front form           | round             |
| IP front protection  | IP66, IP67, IP69K |
| Mounting cut-out     | Ø 22.5 mm         |
| Dimension            | Ø 40 mm           |
| Front bezel colour   | Silver            |
| Front bezel material | Metal             |
| Front dimension      | Ø 40 mm           |
| Housing colour       | Silver            |
| Housing material     | Metal             |
| Lens colour          | Red               |
| Lens illumination    | non illuminative  |
| Lens material        | Plastic           |
| Lens optics          | opaque            |
| Lens shape           | mushroom-head     |
| Switching action     | Maintained        |
| Weight               | 0.097 kg          |

#### Schaltelement

|                                   |   |
|-----------------------------------|---|
| max. number of switching elements | 6 |
|-----------------------------------|---|


#### Function

Emergency stop switch


# EAO – Your Expert Partner for Human Machine Interfaces

45-2C36.2920.000 - Emergency stop switch - Actuator

## Dimensions



## Mounting cut-outs



## Wiring diagrams



## Additional information

The standard lock: RONIS, T254

Mounting depth, incl. front plate, see chapter drawings

Application as per DIN EN ISO 13850

Application as per DIN EN ISO 13850 and EN 60204-1

Twist to unlock clockwise