

# EAO – Your Expert Partner for Human Machine Interfaces

## 45-2D36.1A20.000 - Illuminated emergency stop switch - Actuator

### 45-2D36.1A20.000 - Illuminated emergency stop switch - Actuator



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Attribute

|                      |                   |
|----------------------|-------------------|
| Design               | raised            |
| Front form           | round             |
| IP front protection  | IP66, IP67, IP69K |
| Mounting cut-out     | Ø 22.5 mm         |
| Dimension            | Ø 60 mm           |
| Front bezel colour   | Black             |
| Front bezel material | Plastic           |
| Front dimension      | Ø 60 mm           |
| Housing colour       | Yellow            |
| Housing material     | Plastic           |
| Lens colour          | Red               |
| Lens illumination    | illuminative      |
| Lens material        | Plastic           |
| Lens optics          | opaque            |
| Lens shape           | mushroom-head     |
| Switching action     | Maintained        |
| Weight               | 0.05 kg           |

#### Schaltelement

|                                   |   |
|-----------------------------------|---|
| max. number of switching elements | 4 |
|-----------------------------------|---|


#### Function

Emergency stop switch


# EAO – Your Expert Partner for Human Machine Interfaces

## 45-2D36.1A20.000 - Illuminated emergency stop switch - Actuator


### Dimensions



### Mounting cut-outs



### Wiring diagrams



### Additional information

Mounting depth, incl. front plate, see chapter drawings

Application as per DIN EN ISO 13850

Application as per DIN EN ISO 13850 and EN 60204-1

Twist to unlock clockwise