


EAO – Your Expert Partner for Human Machine Interfaces

61-3440.4/2 - Stop switch actuator

61-3440.4/2 - Stop switch actuator



Attention: The preview is based on a sample product. This can differ from your current configuration.

Mounting

| | |
|------------------|---------|
| Mounting cut-out | Ø 16 mm |
| Design | raised |

Front

| | |
|-----------------|---------|
| Front shape | round |
| Front dimension | Ø 27 mm |

Other Attributes

| | |
|---------|---------------|
| Marking | Stop + Arrows |
| Weight | 0,02 kg |

Operating-/Indication part

| | |
|-------------------|------------------|
| Lens material | Plastic |
| Lens colour | red |
| Lens profile | Mushroom |
| Lens illumination | non-illuminative |
| Lens optics | opaque |

IP-Rating

| | |
|------------------|------|
| Front protection | IP65 |
|------------------|------|

Actuator

| | |
|------------------|------------|
| Switching action | Maintained |
| Housing colour | yellow |
| Housing material | Plastic |

Switching element

| | |
|-----------------------------------|---|
| max. number of switching elements | 1 |
|-----------------------------------|---|


Function

| |
|-------------|
| Stop switch |
|-------------|

EAO – Your Expert Partner for Human Machine Interfaces


61-3440.4/2 - Stop switch actuator

Dimensions




L1 = Solder/Plug-in terminal 2.8 x 0.5 mm

Mounting cut-outs



Wiring diagram



Additional information

Twist to unlock clockwise
Position indication ring black

Legend

Switching action: C = Maintained