
# EAO – Your Expert Partner for **Human Machine Interfaces**

# 704.032.418 - Illuminated pushbutton actuator

#### 704.032.418 - Illuminated pushbutton actuator



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Mounting

 $\begin{array}{ll} \mbox{Mounting cut-out} & \mbox{$\varnothing$ 30,5$ mm} \\ \mbox{Design} & \mbox{flush} \\ \end{array}$ 

#### **Front**

Front shape round
Front dimension Ø 35 mm
Front bezel colour natural anodized
Front bezel material Aluminium

#### Other Attributes

Weight 0.067 kg

## Operating-/Indication part

Lens optics transparent
Lens material Plastic
Lens colour yellow
Lens profile flat
Lens illumination illuminative

#### **IP-Rating**

Front protection IP65

## **Connection Method**

Terminal Screw terminal

#### **Actuator**

Switching action Momentary
Housing material Plastic
Housing colour grey

#### Switching element

max. number of switching 3

elements

# Illumination

LED colour yellow

#### **Function**

Illuminated pushbutton


eao

Stand: 20.05.2024

# EAO – Your Expert Partner for **Human Machine Interfaces**


# 704.032.418 - Illuminated pushbutton actuator

## **Dimensions**




X = Screw terminal

# **Mounting cut-outs**



PIT = Push-in terminal

## Wiring diagram



#### **Additional information**

Max. 3 switching elements can be clipped on The colour of anodized aluminium parts can vary due to technical production reasons

#### Legend

Switching action: B = Momentary