# EAO – Your Expert Partner for **Human Machine Interfaces**

### 61-6441.4077 - Emergency stop switch compact, foolproof EN IEC 60947-5-5

## 61-6441.4077 - Emergency stop switch compact, foolproof EN IEC 60947-5-5



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Mounting

 $\begin{array}{ll} \mbox{Mounting cut-out} & \mbox{$\varnothing$ 16 mm} \\ \mbox{Design} & \mbox{raised} \end{array}$ 

#### **Front**

Front shape round Front dimension Ø 27 mm

#### **Other Attributes**

Marking Arrows Weight 0.018 kg

#### Operating-/Indication part

Lens material Plastic
Lens colour red
Lens profile Mushroom

#### **IP-Rating**

Front protection IP67, IP69K

#### **Connection Method**

Terminal Solder 2.8 x 0.5 mm

#### **Actuator**

Switching action Maintained

#### **Switching element**

Contacts 1 NC + 1 NO

#### **Function**


Emergency stop switch

eao 🔳

# EAO – Your Expert Partner for **Human Machine Interfaces**


### 61-6441.4077 - Emergency stop switch compact, foolproof EN IEC 60947-5-5

#### **Dimensions**




L1 = Solder/Plug-in terminal 2.8 x 0.5 mm

#### **Mounting cut-outs**



#### Wiring diagram



#### **Component layout**



#### **Additional information**

Twist to unlock clockwise Position indication ring green Application as per DIN EN ISO 13850 and EN 60204-1

#### Legend

Switching action: C = Maintained

Stand: 17.05.2024